

SPACERACK PALLET RACKING COMPONENTS



Pallet Racking, Longspan
Shelving and Heavy Duty
Shelving for All Uses

www.spacerack.com.au
150 Station Road, Yeerongpilly,
Queensland, 4105
PH: 07 3426 0900

GRAPHIC	NAME	DESCRIPTION	Code	Size
	SPLICE KIT STD	Splice kits connect two posts end to end. NOTE – Splice kits include all hardware required.		
	SPLICE PLATE STD	Splice plates are used in splice kits.	80300	
	FOOTPLATE BRKT TYPE	Bracket type footplates are used when extra rigidity is required. For example – if a frame system's height to depth ratio is greater than 6:1.	80003	130x100x5
	FOOTPLATE HD TYPE	Heavy Duty type footplates are used when frame loads are expected to be over 7000kg.	80001	130x100x5
	FOOTPLATE STD TYPE	Standard footplates are used on most applications	80000	136x98.5x3
	PALLET RACK TOP CAP	These plastic caps slot into our selective posts to provide a safety cap for the top. Requires M10x60 Bolt(90051) and M10 Flange Nut (90062)	80900	
	SPACER	Spacers keep the rear flange of the post section square in the construction of frames, splice kits, and stand-offs.	90000 90001 90002	36mm 41mm 69mm

SPACERACK PALLET RACKING COMPONENTS



Pallet Racking, Longspan
Shelving and Heavy Duty
Shelving for All Uses

www.spacerack.com.au
150 Station Road, Yeerongpilly,
Queensland, 4105
PH: 07 3426 0900

GRAPHIC	NAME	DESCRIPTION	Code	Size
	GALVANISED SPRING CLIP >> OLD STYLE <<	These spring clips are used with the now superseded style of lockend	90202	
	GALVANISED SPRING CLIP >> NEW STYLE <<	Spring clips ensure beams do not unclip as a result of upward vertical impacts	90201	
	ROW SPACER – TUBULAR	Row spacers tie two frames together. This type can be used on STD, BFS, and Longspan frames.	25998S 25003 25004	380mm 450mm 600mm
	ROW SPACER – BRACING TYPE (WALL TIE)	Row spacers tie two frames together. This type can also be used as a wall tie.	25203 25204 25205	380mm 450mm 60mm
	STAND OFF SPACER	Stand off spacers connect a frame to single post. Note – the stand off length indicates the measurement from one post face to the next.	25503 25505 25560	300mm 600mm 900mm 1200mm 1500mm
	PALLET SUPPORT BAR 50mm x 50mm	Pallet support bars span between two beams to support unusually sized pallets.	26201 26203	850mm 1050mm 1220mm
	FORK CLEARANCE BAR 75mm x 50mm	Fork clearance bars span between two beams to support unpalletised loads.	26301 26303 26304	850mm 1050mm 1220mm
	PARTICLE BOARD SUPPORT BAR LIGHT DUTY 20mm x 20mm	Particle board support bars span between two beams to support board used for a shelf level.	26001 26003 26004	850mm 1050mm 1220mm

SPACERACK PALLET RACKING COMPONENTS



Pallet Racking, Longspan
Shelving and Heavy Duty
Shelving for All Uses

www.spacerack.com.au
150 Station Road, Yeerongpilly,
Queensland, 4105
PH: 07 3426 0900

GRAPHIC	NAME	DESCRIPTION	Code	Size
	PARTICLE BOARD SUPPORT BAR HEAVY DUTY 50mm x 50mm	Particle board support bars span between two beams to support board used for a shelf level.	26103 26105 26107	850mm 1050mm 1220mm
	POST PROTECTOR – POST TYPE 914 HIGH	Post protectors guard the racking from minor impacts. This type is manufactured from a length of post coupled with a special small stand-off.	27000	9144mm
	POST PROTECTOR – ANGLE TYPE 1000 HIGH	Post protectors guard the racking from minor impacts. This type is manufactured from 75x75 angle	27200	1000mm
	POST PROTECTOR – CORNER TYPE 450 HIGH	Post protectors guard the racking from minor impacts. This corner type is commonly used on frames that are on the end of the run, and therefore at greater risk from impact at a number of angles.	27400	450mm
	Z CLIP	Z Clips are placed between the beam and particle board to restrain movement of the shelf	90102	
	J LOCK	J Locks clip into posts to hold spindle pipe used in cable racking.	60088	
	SWL SIGN CORFLUTE 600x300	SWL signs are required if racking installations are - higher than 4.5 m, cover a floor area greater than 300m ² , or have a unit load larger than 1020 kg.	60104	

SPACERACK PALLET RACKING COMPONENTS



Pallet Racking, Longspan
Shelving and Heavy Duty
Shelving for All Uses

www.spacerack.com.au
150 Station Road, Yeerongpilly,
Queensland, 4105
PH: 07 3426 0900

GRAPHIC	NAME	DESCRIPTION	Code	Size
	BENT PIN	Bent pins can be used instead of spring clips to ensure beams do not unclip.	90100	
	STAND OFF ASSEMBLY	Stand Off's connect a frame to a single post. This type incorporates our tubular row spacer. Price does not include Tubular Row Space.		
	STAND OFF BRACKET	The brackets used in Stand Off Assemblies. (See above).		
	WALL TIE ASSEMBLY	This assembly can be used to tie a frame to a wall. This type incorporates our tubular row spacer. Price does not include Tubular Row Space.		
	WALL TIE BRACKET	The bracket used in Wall Tie Assemblies. (See above).		
	DYNABOLT	M12 x 60	90151	
	SHIMS	Shims are packed underneath footplates to ensure frames are plumb on uneven floors. Available in 1.6mm, 3mm and 5mm thicknesses	80100 80101 80102	1.66mm 3.00mm 5.00mm